



## SAFETY DATA SHEET Cellulose Sanding Sealer

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Cellulose Sanding Sealer  
 APPLICATION Air drying paint/lacquer product for interior use  
 SUPPLIER Chestnut Products  
 PO BOX 536  
 Ipswich  
 IP4 5WN  
 Tel. +44 (0) 1473 425878  
 Fax. + 44 (0) 1473 431096  
 CONTACT PERSON mailroom@chestnutproducts.co.uk  
 EMERGENCY TELEPHONE + 44 (0) 1473 425878 (09:00 - 17:00 Mon to Fri)

### 2 HAZARDS IDENTIFICATION

Highly flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Irritating to eyes.

CLASSIFICATION Xi;R36. F;R11. R66, R67.

#### PHYSICAL AND CHEMICAL HAZARDS

The product is highly flammable, and explosive vapours/air mixtures may be formed even at normal room temperatures.

#### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTYL ACETATE -norm	204-658-1	123-86-4	10-25%	R10 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-25%	F;R11 Xi;R36 R66 R67
ISOBUTYL ACETATE	203-745-1	110-19-0	10-25%	F;R11 R66
PROPAN-2-OL	200-661-7	67-63-0	25-50%	F;R11 Xi;R36 R67
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC; LOW BOILING POINT NAPHTHA	265-199-0	64742-95-6	<2.5%	Xn;R65. N;R51/53. R10,R66,R67.
UREA, POLYMER WITH FORMALDEHYDE, ISOBUTYLATED		68002-18-6	2.5-10%	R53.

The Full Text for all R-Phrases are Displayed in Section 16

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Get medical attention. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

#### INHALATION

Move the exposed person to fresh air at once. Perform artificial respiration if breathing has stopped. Keep the affected person warm and at rest. Get prompt medical attention.

## Cellulose Sanding Sealer

### INGESTION

Immediately rinse mouth and provide fresh air. DO NOT induce vomiting. Get medical attention immediately.

### SKIN CONTACT

Wash skin with soap and water. Get medical attention if any discomfort continues.

### EYE CONTACT

Immediately rinse with water. Continue to rinse for at least 15 minutes. Make sure to remove any contact lenses from the eyes before rinsing. Get medical attention promptly if symptoms occur after washing.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

Foam, carbon dioxide or dry powder.

### SPECIAL FIRE FIGHTING PROCEDURES

Do not use water jet as an extinguisher, as this will spread the fire.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Cool containers exposed to flames with water until well after the fire is out. Dike and collect extinguishing water.

### SPECIFIC HAZARDS

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Provide ventilation and confine spill. Do not allow runoff to sewer.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Use only in well-ventilated areas. The product contains organic solvents which will evaporate easily from all surfaces. Take precautionary measures against static discharges. Ground container and transfer equipment to eliminate static electric sparks. Anti-static boots. Keep away from sources of ignition - No smoking. Do not eat, drink or smoke when using the product.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking. Avoid exposure to high temperatures or direct sunlight.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

### Cellulose Sanding Sealer

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
		ppm	mg/m3	ppm	mg/m3	
BUTYL ACETATE -norm	WEL	150	724	200	966	
ETHYL ACETATE	WEL	200		400		
ISOBUTYL ACETATE	WEL	150	724	187	903	
PROPAN-2-OL	WEL	400	999	500	1250	

WEL = Workplace Exposure Limit.

**PROTECTIVE EQUIPMENT**



**RESPIRATORY EQUIPMENT**

Avoid inhalation of vapours. In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2).

**HAND PROTECTION**

Use barrier creams to prevent skin contact. For prolonged or repeated skin contact use suitable protective gloves. Nitrile gloves are recommended.

**EYE PROTECTION**

Avoid contact with eyes. Wear approved chemical safety goggles where eye exposure is reasonably probable.

**HYGIENE MEASURES**

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

**SKIN PROTECTION**

Wear apron or protective clothing in case of splashes.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Viscous liquid		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	>1	VAPOUR PRESSURE	<110 kPa
FLASH POINT (°C)	<=21°C		

## 10 STABILITY AND REACTIVITY

**STABILITY**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition.

## 11 TOXICOLOGICAL INFORMATION

**INHALATION**

Vapours may cause drowsiness and dizziness.

**INGESTION**

Irritating. May cause nausea, stomach pain and vomiting.

**SKIN CONTACT**

Repeated exposure may cause skin dryness or cracking.

## Cellulose Sanding Sealer

**EYE CONTACT**

Irritating to eyes.

**HEALTH WARNINGS**

In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

**TARGET ORGANS**

Mucous membranes. Central nervous system. Respiratory system, lungs. Kidneys. Liver.

**MEDICAL SYMPTOMS**

Narcotic effect.

### 12 ECOLOGICAL INFORMATION

**ECOTOXICITY**

There are no data on the ecotoxicity of this product. Do not allow to enter drains, sewers or watercourses.

**WATER HAZARD CLASSIFICATION**

WGK 1

### 13 DISPOSAL CONSIDERATIONS

**GENERAL INFORMATION**

Do not discharge into drains, water courses or onto the ground.

**DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Do not allow runoff to sewer, waterway or ground.

### 14 TRANSPORT INFORMATION



UK ROAD CLASS	3	UK ROAD PACK GR.	II
PROPER SHIPPING NAME	PAINT	ADR CLASS	Class 3: Flammable liquids.
UN NO. ROAD	1263	TUNNEL RESTRICTION CODE	(D/E)
ADR CLASS NO.	3	ADR LABEL NO.	3
ADR PACK GROUP	II	UN NO. SEA	1263
HAZARD NO. (ADR)	33 Highly flammable liquid (flash-point below 23°C).	IMDG PACK GR.	II
HAZCHEM CODE	•3YE	UN NO. AIR	1263
IMDG CLASS	3	AIR PACK GR.	II
EMS	F-E, S-E		
ICAO CLASS	3		

### 15 REGULATORY INFORMATION

**LABELLING**

## Cellulose Sanding Sealer



Irritant



Highly Flammable

**RISK PHRASES**

- R11 Highly flammable.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

**SAFETY PHRASES**

- S2 Keep out of the reach of children
- S16 Keep away from sources of ignition - No smoking.
- S24/25 Avoid contact with skin and eyes.
- S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S46 If swallowed, seek medical advice immediately and show this container or label.
- S51 Use only in well-ventilated areas.
- S56 Dispose of this material and its container to hazardous or special waste collection point.

**UK REGULATORY REFERENCES**

Health and Safety at Work Act 1974. Chemicals (Hazard Information & Packaging) Regulations.

**EU DIRECTIVES**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

**STATUTORY INSTRUMENTS**

Control of Substances Hazardous to Health.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply.

### 16 OTHER INFORMATION

REVISION DATE 15/12/2009

REV. NO./REPL. SDS GENERATED 4

**RISK PHRASES IN FULL**

- R10 Flammable.
- R11 Highly flammable.
- R36 Irritating to eyes.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R53 May cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

## Cellulose Sanding Sealer

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.